



20208 Pro-Line Diesel Intake System Cleaner

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Issue date: 6/3/2024 Revision date: 6/3/2024 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : 20208 Pro-Line Diesel Intake System Cleaner
Product code :

1.2. Recommended use and restrictions on use

Recommended use : Automotive Care Products.
Restrictions on use : None known

1.3. Supplier

Liqui Moly GmbH
Jerg-Wieland-Strasse 4 Ulm D-89081 Germany
T +49 731 1420 0
info@liqui-moly.de - www.liqui-moly.us

1.4. Emergency telephone number

Emergency number : INFOTRAC
+1800 535 5053 (USA, Canada); +1352 323 3500 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable aerosol Category 1	H222	Extremely flammable aerosol
Gases under pressure Compressed gas	H280	Contains gas under pressure; may explode if heated
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Eye irritation Category 2A	H319	Causes serious eye irritation
Carcinogenicity Category 2	H351	Suspected of causing cancer
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness
Aspiration hazard Category 1	H304	May be fatal if swallowed and enters airways
Hazardous to the aquatic environment – Acute Hazard Category 2	H401	Toxic to aquatic life
Hazardous to the aquatic environment – Chronic Hazard Category 2	H411	Toxic to aquatic life with long lasting effects

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H222 - Extremely flammable aerosol
H280 - Contains gas under pressure; may explode if heated
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness

20208 Pro-Line Diesel Intake System Cleaner

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Precautionary statements (GHS US)

- H351 - Suspected of causing cancer
- H411 - Toxic to aquatic life with long lasting effects
- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 - Do not spray on an open flame or other ignition source.
- P251 - Pressurized container: Do not pierce or burn, even after use.
- P261 - Avoid breathing spray, vapors.
- P264 - Wash hands thoroughly after handling.
- P271 - Use only outdoors or in a well-ventilated area.
- P273 - Avoid release to the environment.
- P280 - Wear eye protection, protective gloves.
- P301+P310 - If swallowed: Immediately call a POISON CENTER, a doctor.
- P331 - Do NOT induce vomiting.
- P302+P352 - If on skin: Wash with plenty of soap and water.
- P332+P313 - If skin irritation occurs: Get medical advice/attention.
- P362+P364 - Take off contaminated clothing and wash it before reuse.
- P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
- P312 - Call a POISON CENTER, a doctor if you feel unwell.
- P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313 - If eye irritation persists: Get medical advice/attention.
- P308+P313 - If exposed or concerned: Get medical advice/attention.
- P391 - Collect spillage.
- P405 - Store locked up.
- P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- P501 - Dispose of contents/container to an approved waste disposal plant.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None known.

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Acetone	CAS-No.: 67-64-1	30 – 60
Solvent naptha (petroleum), heavy arom.	CAS-No.: 64742-94-5	30 – 60
Naphthalene	CAS-No.: 91-20-3	<0.5

Comments : *Chemical name, CAS number and/or exact concentration have been withheld as a trade secret
Full text of hazard classes and H-statements : see section 16

20208 Pro-Line Diesel Intake System Cleaner

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Wash skin with mild soap and water. Get medical advice if skin irritation persists.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Get medical attention if irritation develops and persists.
First-aid measures after ingestion	: If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.
Inhalation	: Inhalation may affect the nervous system causing headache, possibly dizziness, nausea, weakness, loss of coordination and unconsciousness.
Skin	: Causes skin irritation. Repeated or prolonged skin contact may cause dermatitis and defatting.
Eyes	: Causes serious eye irritation.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. May be fatal if swallowed and enters airways.
Chronic symptoms	: Suspected of causing cancer.

4.3. Immediate medical attention and special treatment, if necessary

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Use of heavy stream of water may spread fire.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: vapors may form explosive mixture with air. Pressurized container: may burst if heated.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon oxides (CO, CO ₂). Fire will produce dense black smoke.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Cool down the containers exposed to heat with a water spray. Use shielding to protect from bursting cans.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate all ignition sources. Ventilate spillage area. Use explosion-proof equipment.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Eliminate ignition sources. Avoid contact with eyes, skin and clothing. Keep unnecessary and unprotected personnel away from the spillage.
----------------------	---

20208 Pro-Line Diesel Intake System Cleaner

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Leaking cans should be placed in a plastic bag or open pail until the pressure has dissipated. Absorb and/or contain spill with inert material, then place in suitable container. Use non-sparking tools.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with eyes, skin and clothing. Avoid breathing vapors, spray. Take precautionary measures against static discharge. Do not puncture or incinerate containers.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Store away from heat. Protect from sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Incompatible materials : Strong oxidizers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Acetone (67-64-1)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Acetone
ACGIH OEL TWA	250 ppm
ACGIH OEL STEL	500 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2024
USA - ACGIH - Biological Exposure Indices	
Local name	Acetone

20208 Pro-Line Diesel Intake System Cleaner

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Acetone (67-64-1)	
BEI (BLV)	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift - Notations: Ns
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Acetone
OSHA PEL (TWA)	2400 mg/m ³
	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Naphthalene (91-20-3)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Naphthalene
ACGIH OEL TWA	10 ppm
Remark (ACGIH)	TLV® Basis: URT irr; cararacts; hemolytic anemia. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2024
USA - ACGIH - Biological Exposure Indices	
Local name	Naphthalene
BEI (BLV)	Parameter: 1-Naphthol + 2-Naphthol (with hydrolysis) - Sampling time: End of shift - Notations: Nq, Ns
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Naphthalene
OSHA PEL (TWA)	50 mg/m ³
	10 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
8.2. Appropriate engineering controls	
Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.
8.3. Individual protection measures/Personal protective equipment	
Hand protection:	
Chemically resistant protective gloves. Consult supplier for specific recommendations.	
Eye protection:	
Avoid contact with eyes. Chemical goggles or safety glasses	
Skin and body protection:	
Wear suitable protective clothing	

20208 Pro-Line Diesel Intake System Cleaner

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Respiratory protection:

In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid. Aerosol can.
Color	: Yellow
Odor	: Characteristic
Odor threshold	: No data available
pH	: Not applicable
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: -17 °C (1.4°F) (acetone)
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.829
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: < 7 mm ² /s @40°C
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: None.
Oxidizing properties	: None.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong oxidizers. Strong acids. Strong bases.

20208 Pro-Line Diesel Intake System Cleaner

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg
LC50 Inhalation - Rat	76 mg/l
ATE US (oral)	5800 mg/kg body weight
ATE US (vapors)	76 mg/l/4h
ATE US (dust, mist)	76 mg/l/4h

Solvent naptha (petroleum), heavy arom. (64742-94-5)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: other:EPA Fed Reg Vol 50, No. 188 1985 and as amended in Fed Reg Vol 52, No. 97, 1987
LC50 Inhalation - Rat	> 5.28 mg/l/4h

Naphthalene (91-20-3)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LD50 dermal rabbit	2500 mg/kg Source: ChemIDplus
LC50 Inhalation - Rat	> 0.4 mg/l/4h Animal: rat, Guideline: other:EPA TSCA, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
LC50 Inhalation - Rat (Vapours)	> 0.4 mg/l Source: ECHA

Skin corrosion/irritation : Causes skin irritation.
pH: Not applicable
Serious eye damage/irritation : Causes serious eye irritation.
pH: Not applicable
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Suspected of causing cancer.

Naphthalene (91-20-3)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	Reasonably anticipated to be Human Carcinogen

Reproductive toxicity : Not classified

Acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg body weight mouse
NOAEL (animal/male, F0/P)	900 mg/kg body weight rat

20208 Pro-Line Diesel Intake System Cleaner

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Solvent naptha (petroleum), heavy arom. (64742-94-5)	
NOAEL (animal/male, F0/P)	35 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:OPPTS 870.3650 Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test
NOAEL (animal/female, F0/P)	125 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:OPPTS 870.3650 Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test
Naphthalene (91-20-3)	
LOAEL (animal/female, F0/P)	50 mg/kg body weight Animal: rat, Animal sex: female, Guideline: other:OECD Guideline 414 (Prenatal Developmental Toxicity Study)
LOAEL (animal/female, F1)	450 mg/kg body weight Animal: rat, Animal sex: female, Guideline: other:OECD Guideline 414 (Prenatal Developmental Toxicity Study)
NOAEL (animal/female, F0/P)	120 mg/kg body weight Animal: rabbit, Animal sex: female, Guideline: other:OECD Guideline 414 (Prenatal Developmental Toxicity Study)
STOT-single exposure	: May cause drowsiness or dizziness.
Acetone (67-64-1)	
STOT-single exposure	: May cause drowsiness or dizziness.
Solvent naptha (petroleum), heavy arom. (64742-94-5)	
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Solvent naptha (petroleum), heavy arom. (64742-94-5)	
LOAEC (inhalation, rat, vapor, 90 days)	4.71 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity: 90-Day Study)
NOAEL (oral, rat, 90 days)	750 mg/kg body weight Animal: rat, Animal sex: female
NOAEC (inhalation, rat, vapor, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity: 90-Day Study)
Naphthalene (91-20-3)	
LOAEL (oral, rat, 90 days)	400 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
LOAEC (inhalation, rat, vapor, 90 days)	0.011 mg/l air Animal: rat, Guideline: EPA OPP 82-4 (90-Day Inhalation Toxicity), Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (oral, rat, 90 days)	200 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
Aspiration hazard	: May be fatal if swallowed and enters airways.
Viscosity, kinematic	: < 7 mm²/s @40°C
Solvent naptha (petroleum), heavy arom. (64742-94-5)	
Viscosity, kinematic	1 – 2.4 mm²/s at 40°C
Symptoms/effects	: May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.
Inhalation	: Inhalation may affect the nervous system causing headache, possibly dizziness, nausea, weakness, loss of coordination and unconsciousness.

20208 Pro-Line Diesel Intake System Cleaner

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Skin	: Causes skin irritation. Repeated or prolonged skin contact may cause dermatitis and defatting.
Eyes	: Causes serious eye irritation.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. May be fatal if swallowed and enters airways.
Chronic symptoms	: Suspected of causing cancer.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Acetone (67-64-1)	
NOEC (chronic)	≥ 79 mg/l Daphnia magna (Water flea)
Solvent naptha (petroleum), heavy arom. (64742-94-5)	
LC50 - Fish [1]	2 mg/l
EC50 - Crustacea [1]	1.4 mg/l
EC50 72h - Algae [1]	3.7 mg/l
NOEC (chronic)	0.48 mg/l
Naphthalene (91-20-3)	
LC50 - Fish [1]	7.8 mg/l
EC50 - Crustacea [1]	2.16 mg/l Test organisms (species): Daphnia magna
LC50 - Fish [2]	1.6 mg/l
EC50 72h - Algae [1]	2.9 mg/l
EC50 72h - Algae [2]	0.4 mg/l
NOEC (chronic)	0.59 mg/l Test organisms (species): Daphnia pulex Duration: '125 d'
NOEC chronic fish	0.12 mg/l Test organisms (species): Oncorhynchus mykiss

12.2. Persistence and degradability

20208 Pro-Line Diesel Intake System Cleaner	
Persistence and degradability	No data available.
Acetone (67-64-1)	
Persistence and degradability	Readily biodegradable.
Solvent naptha (petroleum), heavy arom. (64742-94-5)	
Persistence and degradability	Not readily biodegradable.
Naphthalene (91-20-3)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

Solvent naptha (petroleum), heavy arom. (64742-94-5)	
Partition coefficient n-octanol/water (Log Pow)	2.9 – 6.1 Source: IUCLID

20208 Pro-Line Diesel Intake System Cleaner

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Naphthalene (91-20-3)

Partition coefficient n-octanol/water (Log Pow) 3.3 Source: hsb

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
1950	UN1950	1950	1950
14.2. Proper Shipping Name			
Aerosols	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1
	 Not applicable		
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
Note: Inner packages containing net quantities of less than 5 kg/5 L are exempt per IMDG Code 2.10.2.7 and ICAO Special Provision A197.			

14.6. Special precautions for user

DOT
UN-No.(DOT) : UN1950
DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

20208 Pro-Line Diesel Intake System Cleaner

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials
TDG	
UN-No. (TDG)	: UN1950
TDG Special Provisions	: 80 - Despite section 1.17 of Part 1, Coming into Force, Repeal, Interpretation, General Provisions and Special Cases, a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with section 5.11 of Part 5, Means of Containment, except that the requirement in subsection 5.11(6) for aerosol containers to be tightly packed in a wood, fibreboard or plastic box does not apply to a user or purchaser who transports no more than six aerosol containers. Note that subsection 5.11(6) includes two requirements, one for a valve protection cap and one for containment, and that the exemption for aerosol containers in special provision 80 applies only to the containment requirement in that subsection; the requirement for a valve protection cap continues to apply. For a similar rule respecting aerosol containers, see subparagraph 1.15(1)(a)(i) of Part 1, Coming into Force, Repeal, Interpretation, General Provisions and Special Cases, 107 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2, (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a ship on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray. SOR/2014-306 UN1950, UN2037 SOR/2014-306
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L
Emergency Response Guide (ERG) Number	: 126
IMDG	
Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69
IATA	
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provision (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

20208 Pro-Line Diesel Intake System Cleaner

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

SECTION 15: Regulatory information

15.1. US Federal regulations

20208 Pro-Line Diesel Intake System Cleaner

SARA Section 311/312 Hazard Classes	Refer to Section 2 for OSHA Hazard Classification.
-------------------------------------	--

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Acetone (67-64-1)

CERCLA RQ	5000 lb
-----------	---------

Naphthalene (91-20-3)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	100 lb
-----------	--------

15.2. International regulations

CANADA

Acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

Solvent naptha (petroleum), heavy arom. (64742-94-5)

Listed on the Canadian DSL (Domestic Substances List)

Naphthalene (91-20-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

20208 Pro-Line Diesel Intake System Cleaner

Listed on the Canadian DSL (Domestic Substances List)

Naphthalene (91-20-3)

Listed on IARC (International Agency for Research on Cancer)
Listed as carcinogen on NTP (National Toxicology Program)

15.3. US State regulations



WARNING:

This product can expose you to Naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

20208 Pro-Line Diesel Intake System Cleaner

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Component	State or local regulations
Acetone(67-64-1)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - New Jersey - Right to Know Hazardous Substance List
Naphthalene(91-20-3)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Revision date : 6/3/2024

Data sources : This safety data sheet was compiled with data and information from the following sources : RTECS, ECOSAR, HSDB, SIDS SIAP, CESAR, Chemical DB.

Full text of H-phrases	
H222	Extremely flammable aerosol
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.