



22074 Pro-Line Turbocharger Additive

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)
Issue date: 8/11/2026 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : 22074 Pro-Line Turbocharger Additive
Product code :

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Lubricant
Recommended use : Lubricant
Restrictions on use : None known

1.4. Supplier's details

Manufacturer

Liqui Moly GmbH
Jerg-Wieland-Strasse 4 Ulm D-89081 Germany
T +49 731 1420 0
info@liqui-moly.de - www.liqui-moly.us

Distributor

LIQUI MOLY USA Inc.
62-64 Enter Lane
Islandia, New York 11749
USA
T (888)665-9645

1.5. Emergency phone number

Emergency number : INFOTRAC
+1800 535 5053 (USA, Canada); +1352 323 3500 (International)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Hazardous to the aquatic environment — Acute Hazard, Category 3	H402	Harmful to aquatic life.
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412	Harmful to aquatic life with long lasting effects.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard statements (GHS US) : H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (GHS US) : P273 - Avoid release to the environment.
P501 - Dispose of contents and/or container to an approved waste disposal plant.

2.3. Hazards associated with known or reasonably anticipated uses

None known

2.4. Hazards not otherwise classified

Other hazards which do not result in classification : None known.

2.5. Unknown acute toxicity

No additional information available

22074 Pro-Line Turbocharger Additive

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

SECTION 3 Composition/information on ingredients

Mixtures

Name	Product identifier	Conc. (% w/w)
Highly refined mineral oil (C15-C50)	CAS-No.: Proprietary	15 - 40*
Reaction product of cocoalkyldiethanolamides and cocoalkylmonoglycerides and molybdenumtrioxide	CAS-No.: 445409-27-8	15 - 40*
Distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	5 - 10*
Di-tert-Bu Polysulfides	CAS-No.: 68937-96-2	7 - 13*
zinc O,O',O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate)	CAS-No.: 2215-35-2	3 - 7*
Benzenesulfonic acid, mono-C20-24 (even)-sec-alkyl derivs., para-, sodium salts	CAS-No.: 946-212-5	1 - 5*
Distillates (petroleum), hydrotreated heavy naphthenic	CAS-No.: 64742-52-5	1 - 5*
Dibutyl phosphonate	CAS-No.: 1809-19-4	1 - 5*

Comments : *Chemical name, CAS number and/or exact concentration have been withheld as a trade secret
Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with mild soap and water.
First-aid measures after eye contact : Rinse immediately with plenty of water. Get medical attention if irritation develops and persists.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects : Causes serious eye irritation.
Inhalation : Inhalation of mists or vapors at elevated temperatures may cause respiratory irritation.
Skin : Repeated or prolonged skin contact may cause dermatitis and defatting.
Eyes : May cause minor eye irritation.
Ingestion : Abdominal pain. Diarrhoea.
Chronic symptoms : None known.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Use of heavy stream of water may spread fire.

5.2. Specific hazards arising from the chemical

Fire hazard : This product is not classified as flammable or combustible.
Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon oxides (CO, CO₂). Sulfur oxides (SO_x). Phosphorus oxides. Fire will produce dense black smoke.

22074 Pro-Line Turbocharger Additive

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Cool down the containers exposed to heat with a water spray.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Emergency procedures	: Keep unnecessary and unprotected personnel away from the spillage.
----------------------	--

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Environmental precautions	: Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Absorb and/or contain spill with inert material, then place in suitable container.
Other information	: Dispose of materials or solid residues at an authorized site.
For further information refer to section 13.	

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with eyes. Avoid repeated or prolonged skin contact.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions	: Store in a well-ventilated place. Keep cool.
Incompatible materials for storage	: Strong oxidizers.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)	
USA - ACGIH® - Threshold Limit Values	
Local name	Mineral oil, excluding metal working fluids Pure, highly and severely refined
ACGIH® TLV® TWA	5 mg/m³ (I - Inhalable particulate matter)
Remark (ACGIH®)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Oil mist, mineral
OSHA PEL (TWA)	5 mg/m³

22074 Pro-Line Turbocharger Additive

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
USA - ACGIH® - Threshold Limit Values	
Local name	Mineral oil, excluding metal working fluids Pure, highly and severely refined
ACGIH® TLV® TWA	5 mg/m³ (I - Inhalable particulate matter)
Remark (ACGIH®)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Oil mist, mineral
OSHA PEL (TWA)	5 mg/m³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Highly refined mineral oil (C15-C50) (Proprietary)	
USA - ACGIH® - Threshold Limit Values	
ACGIH® TLV® TWA	5 mg/m³ inhalable
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA)	5 mg/m³

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection:
In case of repeated or prolonged contact wear gloves. Consult supplier for specific recommendations.
Eye protection:
Use suitable eye protection. Chemical goggles or safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Color : black or gray
Odor : Characteristic
Odor threshold : No data available
pH : Not applicable

22074 Pro-Line Turbocharger Additive

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 100 °C (212°F)
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.998
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: > 20.5 mm²/s @40C
Viscosity, dynamic	: 330 mPa·s @20°C
Explosion limits	: No data available
Explosive properties	: None.
Oxidizing properties	: None.
Particle characteristics	: Particle characteristics : Not applicable

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong oxidizers. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg

22074 Pro-Line Turbocharger Additive

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)	
LC50 Inhalation - Rat	> 5 mg/l
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight
LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
LC50 Inhalation - Rat	> 5000 mg/m³
zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)	
LD50 oral rat	2230 mg/kg body weight Animal: rat, Guideline: other:, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1,66 - 2,99
LD50 dermal rabbit	> 3160 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Dibutyl phosphonate (1809-19-4)	
LD50 oral rat	> 3000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 oral	3200 mg/kg
LD50 dermal rabbit	≈ 5000 mg/kg body weight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 434 (Acute Dermal Toxicity - Fixed Dose Procedure)
LC50 Inhalation - Rat (Vapors)	> 22.5 mg/l/4h
Skin corrosion/irritation	: Not classified pH: Not applicable
Serious eye damage/irritation	: Not classified. pH: Not applicable
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Dibutyl phosphonate (1809-19-4)	
NOAEL (chronic,oral,animal/male,2 years)	≈ 348 mg/kg body weight Animal: rat, Animal sex: male
NOAEL (chronic,oral,animal/female,2 years)	450 mg/kg body weight Animal: rat, Animal sex: female
Reproductive toxicity	: Not classified
Dibutyl phosphonate (1809-19-4)	
LOAEL (animal/male, F0/P)	375 mg/kg body weight Animal: mouse, Animal sex: male, Guideline: other:
LOAEL (animal/female, F1)	≈ 300 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]
NOAEL (animal/male, F0/P)	190 mg/kg body weight Animal: mouse, Animal sex: male, Guideline: other:
NOAEL (animal/female, F0/P)	≈ 5000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Reaction product of cocoalkyldiethanolamides and cocoalkylmonoglycerides and molybdenumtrioxide (445409-27-8)	
NOAEL (oral,rat,90 days)	150 mg/kg body weight Animal: rat, Guideline: EU Method B.7 (Repeated Dose (28 Days) Toxicity (Oral)), Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)

22074 Pro-Line Turbocharger Additive

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)	
LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Di-tert-Bu Polysulfides (68937-96-2)	
LOAEL (oral, rat, 90 days)	300 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.7 (Repeated Dose (28 Days) Toxicity (Oral))
NOAEL (oral, rat, 90 days)	100 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.7 (Repeated Dose (28 Days) Toxicity (Oral))
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
zinc O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)	
NOAEL (oral, rat, 90 days)	160 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Dibutyl phosphonate (1809-19-4)	
LOAEC (inhalation, rat, vapor, 90 days)	1.3 mg/l air Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
NOAEL (oral, rat, 90 days)	500 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Aspiration hazard : Not classified

22074 Pro-Line Turbocharger Additive	
Viscosity, kinematic	> 20.5 mm²/s @40C
Symptoms/effects	: Causes serious eye irritation.
Inhalation	: Inhalation of mists or vapors at elevated temperatures may cause respiratory irritation.
Skin	: Repeated or prolonged skin contact may cause dermatitis and defatting.
Eyes	: May cause minor eye irritation.
Ingestion	: Abdominal pain. Diarrhoea.
Chronic symptoms	: None known.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Harmful to aquatic life.
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Reaction product of cocoalkyldiethanolamides and cocoalkylmonoglycerides and molybdenumtrioxide (445409-27-8)	
LC50 - Fish [1]	> 10 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	1.5 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	1.5 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	4 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

22074 Pro-Line Turbocharger Additive

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Reaction product of cocoalkyldiethanolamides and cocoalkylmonoglycerides and molybdenumtrioxide (445409-27-8)	
LOEC (chronic)	1.5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.47 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Di-tert-Bu Polysulfides (68937-96-2)	
LC50 - Fish [1]	800 mg/l Source: IUCLID
EC50 - Crustacea [1]	63 mg/l
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	≥ 100 mg/l
EC50 - Crustacea [1]	> 10 g/l
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID
zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)	
LC50 - Fish [1]	4.5 mg/l
EC50 - Crustacea [1]	23 mg/l
ErC50 algae	24 mg/l
NOEC (chronic)	0.4 mg/l Daphnia magna 21d
Dibutyl phosphonate (1809-19-4)	
LC50 - Fish [1]	> 63.4 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	20.8 mg/l
EC50 72h - Algae [1]	≈ 14.4 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≈ 4.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
12.2. Persistence and degradability	
22074 Pro-Line Turbocharger Additive	
Persistence and degradability	Rapidly degradable
Reaction product of cocoalkyldiethanolamides and cocoalkylmonoglycerides and molybdenumtrioxide (445409-27-8)	
Persistence and degradability	Not rapidly degradable
Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)	
Persistence and degradability	Inherently biodegradable.
Di-tert-Bu Polysulfides (68937-96-2)	
Persistence and degradability	Not rapidly degradable
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Inherently biodegradable.
zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)	
Persistence and degradability	Not rapidly degradable

22074 Pro-Line Turbocharger Additive

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Benzenesulfonic acid, mono-C20-24 (even)-sec-alkyl derivs., para-, sodium salts (946-212-5)	
Persistence and degradability	Rapidly degradable
Dibutyl phosphonate (1809-19-4)	
Persistence and degradability	Readily biodegradable, failing 10-day window.
Highly refined mineral oil (C15-C50) (Proprietary)	
Persistence and degradability	No additional information available.

12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
zinc O,O',O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)	
Partition coefficient n-octanol/water (Log Pow)	2.21 Source: ECHA
Dibutyl phosphonate (1809-19-4)	
Partition coefficient n-octanol/water (Log Pow)	1.81 Source: ChemIDplus

12.4. Mobility in soil

Di-tert-Bu Polysulfides (68937-96-2)	
Mobility in soil	9816 Source: EPISUITE

12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No

SECTION 13 Disposal considerations

Waste treatment methods : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated

22074 Pro-Line Turbocharger Additive

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

DOT	TDG	IMDG	IATA
No supplementary information available			

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

Not regulated

TDG

Not regulated

IMDG

Not regulated

IATA

Not regulated

SECTION 15 Regulatory information

15.1. Federal regulations

22074 Pro-Line Turbocharger Additive

SARA Section 311/312 Hazard Classes

Refer to Section 2 for OSHA Hazard Classification.

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Dibutyl phosphonate (1809-19-4)

SARA Section 311/312 Hazard Classes

Refer to Section 2 for OSHA Hazard Classification.

15.2. International regulations

CANADA

Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

Listed on the Canadian DSL (Domestic Substances List)

Di-tert-Bu Polysulfides (68937-96-2)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

22074 Pro-Line Turbocharger Additive

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)

Listed on the Canadian DSL (Domestic Substances List)

Dibutyl phosphonate (1809-19-4)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

22074 Pro-Line Turbocharger Additive

Listed on the Canadian DSL (Domestic Substances List)

Reaction product of cocoalkyldiethanolamides and cocoalkylmonoglycerides and molybdenumtrioxide (445409-27-8)

Listed on the Canadian DSL (Domestic Substances List)

Dibutyl phosphonate (1809-19-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16 Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Issue date : 8/11/2026

Data sources : This safety data sheet was compiled with data and information from the following sources :
ECHA, ECOSAR, HSDB, SIDS SIAP, CESAR, Chemical DB.


Full text of hazard classes and H-statements

H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

NFPA health hazard : 0 - Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.