



7712 Pro-Line Engine Flush

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Issue date: 4/29/2021 Revision date: 3/6/2026 Supersedes: 6/17/2025 Version: 10.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : 7712 Pro-Line Engine Flush
Product code :

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Engine oil,Cleaner
Restrictions on use : None known

1.4. Supplier's details

Liqui Moly GmbH
Jerg-Wieland-Strasse 4 Ulm D-89081 Germany
T +49 731 1420 0
info@liqui-moly.de - www.liqui-moly.us

1.5. Emergency phone number

Emergency number : INFOTRAC
+1800 535 5053 (USA, Canada); +1352 323 3500 (International)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquid, Category 4	H227	Combustible liquid.
Serious eye damage/eye irritation, Category 2A	H319	Causes serious eye irritation.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H227 - Combustible liquid
H304 - May be fatal if swallowed and enters airways
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 - Avoid breathing mist.
P264 - Wash hands thoroughly after handling.

7712 Pro-Line Engine Flush

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves.
P301+P310 - If swallowed: Immediately call a POISON CENTER, a doctor.
P331 - Do NOT induce vomiting.
P302+P352 - If on skin: Wash with plenty of soap and water.
P333+P313 - If skin irritation or rash occurs: Get medical attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical attention.
P370+P378 - In case of fire: Use carbon dioxide (CO2), dry extinguishing powder, foam to extinguish.
P403 - Store in a well-ventilated place.
P405 - Store locked up.
P501 - Dispose of to an approved waste disposal plant to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

None known

2.4. Hazards not otherwise classified

Other hazards which do not result in classification : None known.

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc. (% w/w)
Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	80-100
Highly refined mineral oil (C15-C50)	CAS-No.: Proprietary	1 – 5
Distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	1 – 5
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts	CAS-No.: 68442-22-8	1 – 5
Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts	CAS-No.: 722503-68-6	1 – 5

Comments : *Chemical name, CAS number and/or exact concentration have been withheld as a trade secret
Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact : Wash skin with mild soap and water. If skin irritation or rash occurs: Get medical advice/attention.

7712 Pro-Line Engine Flush

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Get medical attention if irritation develops and persists.
First-aid measures after ingestion	: Aspiration hazard. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration into the lungs. Seek immediate medical advice.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects	: May be fatal if swallowed and enters airways. May cause an allergic skin reaction.
Inhalation	: Inhalation of mists or vapors at elevated temperatures may cause respiratory irritation.
Skin	: May cause an allergic skin reaction. Repeated or prolonged skin contact may cause dermatitis and defatting.
Eyes	: Causes serious eye irritation.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.
Chronic symptoms	: None known.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Treat symptomatically.
-----------------------------------	--

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Use of heavy stream of water may spread fire.

5.2. Specific hazards arising from the chemical

Fire hazard	: Combustible liquid.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon oxides (CO, CO ₂). Fire will produce dense black smoke.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Cool down the containers exposed to heat with a water spray.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate all ignition sources. Avoid contact with eyes, skin and clothing.
For non-emergency personnel	
Emergency procedures	: Keep unnecessary and unprotected personnel away from the spillage.
For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Environmental precautions	: Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Absorb and/or contain spill with inert material, then place in suitable container.
Other information	: Dispose of materials or solid residues at an authorized site.

7712 Pro-Line Engine Flush

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Avoid breathing mist, vapors. Keep away from open flames, hot surfaces and sources of ignition. Do not ingest.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions	: Store in a well-ventilated place. Keep cool. Store product sealed in the original container, away from heat and out of direct sunlight.
Incompatible materials	: Strong oxidizers.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Highly refined mineral oil (C15-C50) (Proprietary)	
USA - ACGIH® - Threshold Limit Values	
ACGIH® TLV® TWA	5 mg/m³ inhalable
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA)	5 mg/m³
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
USA - ACGIH® - Threshold Limit Values	
Local name	Mineral oil, excluding metal working fluids Pure, highly and severely refined
ACGIH® TLV® TWA	5 mg/m³ (I - Inhalable particulate matter)
Remark (ACGIH®)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Oil mist, mineral
OSHA PEL (TWA)	5 mg/m³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection:
In case of repeated or prolonged contact wear gloves. Consult supplier for specific recommendations.

7712 Pro-Line Engine Flush

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Eye protection:
Avoid contact with eyes. Safety glasses with side shields. Chemical goggles
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear. Liquid.
Color	: Brown
Odor	: Characteristic
Odor threshold	: No data available
pH	: Not applicable
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 187 – 216 °C
Flash point	: 63 °C (145.4°F)
Flammability (solid, gas)	: Combustible liquid.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.805
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 3.4 mm²/s @40C
Explosion limits	: Lower explosion limit: 0.7 Vol-% Upper explosion limit: 6 Vol-%
Explosive properties	: None.
Oxidizing properties	: None.
Particle characteristics	: Particle characteristics : Not applicable

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

7712 Pro-Line Engine Flush

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong oxidizers. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Distillates (petroleum), hydrotreated light (64742-47-8)

LD50 oral rat	> 5000 mg/kg
LD50 oral	15000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 6.8 mg/l/4h

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts (68442-22-8)

LD50 oral rat	2000 – 5000 mg/kg body weight Animal: rat, Guideline: other:
LD50 dermal rat	> 2002 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 2000 mg/kg Source: ECHA

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight
LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
LC50 Inhalation - Rat	> 5000 mg/m³

Skin corrosion/irritation : Not classified
pH: Not applicable
Serious eye damage/irritation : Causes serious eye irritation.
pH: Not applicable
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

Distillates (petroleum), hydrotreated light (64742-47-8)

NOAEL (animal/male, F0/P)	≥ 3000 mg/kg body weight
---------------------------	--------------------------

STOT-single exposure : Not classified
STOT-repeated exposure : Not classified

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts (68442-22-8)

NOAEL (oral,rat,90 days)	160 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
--------------------------	--

7712 Pro-Line Engine Flush

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard : May be fatal if swallowed and enters airways.

7712 Pro-Line Engine Flush	
Viscosity, kinematic	3.4 mm²/s @40C
Symptoms/effects	: May be fatal if swallowed and enters airways. May cause an allergic skin reaction.
Inhalation	: Inhalation of mists or vapors at elevated temperatures may cause respiratory irritation.
Skin	: May cause an allergic skin reaction. Repeated or prolonged skin contact may cause dermatitis and defatting.
Eyes	: Causes serious eye irritation.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.
Chronic symptoms	: None known.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Distillates (petroleum), hydrotreated light (64742-47-8)	
LC50 - Fish [1]	2.2 mg/l
EC50 - Crustacea [1]	> 1000 mg/l

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts (68442-22-8)	
LC50 - Fish [1]	46 mg/l Test organisms (species): Cyprinodon variegatus
EC50 - Crustacea [1]	23 mg/l
EC50 72h - Algae [1]	24 mg/l
NOEC chronic crustacea	0.4 mg/l

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	≥ 100 mg/l
EC50 - Crustacea [1]	> 10 g/l
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

12.2. Persistence and degradability

7712 Pro-Line Engine Flush	
Persistence and degradability	No additional information available.
Distillates (petroleum), hydrotreated light (64742-47-8)	
Persistence and degradability	Inherently biodegradable.
Biodegradation	85 % OECD 301F (28d)

7712 Pro-Line Engine Flush

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts (68442-22-8)	
Persistence and degradability	Not readily biodegradable.
Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts (722503-68-6)	
Persistence and degradability	Rapidly degradable
Highly refined mineral oil (C15-C50) (Proprietary)	
Persistence and degradability	No additional information available.
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Inherently biodegradable.

12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No

SECTION 13 Disposal considerations

Waste treatment methods : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
UN1268	Not regulated	Not regulated	Not regulated
14.2. Proper Shipping Name			
Petroleum distillates, n.o.s.	Not regulated	Not regulated	Not regulated
Transport document description			
UN1268 Petroleum distillates, n.o.s., Combustible liquid, III	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Combustible liquid	Not regulated	Not regulated	Not regulated
14.4. Packing group			
III	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Dangerous for the environment: No	Not regulated	Not regulated	Not regulated
The requirements of the US DOT Hazardous Materials Regulations do not apply to a material classed as a combustible liquid in a non-bulk packaging			

7712 Pro-Line Engine Flush

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

DOT	TDG	IMDG	IATA
unless the combustible liquid is a hazardous substance, a hazardous waste, or a marine pollutant.			

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT
UN-No. (DOT) : UN1268

TDG
Not regulated

IMDG
Not regulated

IATA
Not regulated

SECTION 15 Regulatory information

15.1. Federal regulations

7712 Pro-Line Engine Flush	
SARA Section 311/312 Hazard Classes	Refer to Section 2 for OSHA Hazard Classification.

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.		
Zinc Compounds	CAS-No.	1 – 5%

15.2. International regulations

CANADA

Distillates (petroleum), hydrotreated light (64742-47-8)
Listed on the Canadian DSL (Domestic Substances List)

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts (68442-22-8)
Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)
Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations
No additional information available

7712 Pro-Line Engine Flush

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

National regulations

7712 Pro-Line Engine Flush

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts (722503-68-6)

Listed on the Canadian DSL (Domestic Substances List)

15.3. State regulations



WARNING:

This product can expose you to 2-Ethylhexyl acrylate, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Revision date : 3/6/2026

Issue date : 4/29/2021

Data sources : This safety data sheet was compiled with data and information from the following sources :
ECHA, ECOSAR, HSDB, SIDS SIAP, CESAR, Chemical DB.


Full text of hazard classes and H-statements

H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.